



## Marine Series

CONSTRUCTION	
<b>Base Fabric</b>	600D X 600D 100% Solution Dyed Polyester
<b>Finished Fabric Weight</b>	7.25 oz/yd <sup>2</sup> +/- 2.5% (ASTM D3776)
<b>Finishing</b>	Water Repellent + Poly-Urethane + Anti-Microbia
<b>Put Up (Per Roll)</b>	60 yards
<b>Finish Width</b>	60 Inches
<b>Color Available</b>	15 Colors (Specific Color Matching is Acceptable)
<b>Thread Count</b>	≥ 76T (ASTM D3775)
DURABILITY	
<b>UV Resistance</b>	≥Grade 4 Gray Scale against 600 hours (AATCC-186)
<b>Water Proof</b>	900 cm (AATCC-127)
<b>Tear Strength</b>	24 x 20 lbs (ASTM D2261)
<b>Tensile Strength</b>	370 x 250 lbs (ASTM D5034)
<b>Crocking</b>	(Wet/Dry Face and Back) ≥ 4.5 Grade (AATCC 8)
<b>Spray Test</b>	100 (AATCC 22)
<b>Anti-Mildew</b>	100% Surface Inhibition (ASTM G21)
<b>Crocking</b>	(Wet/Dry Face and Back) ≥ 4.5 Grade (AATCC 8)
<b>Application</b>	boat covers, bimini tops, boat storage covers, furniture covers, tonneau covers, luggage, and camping enclosures etc